

# Medical Refrigeration

## Bromic MediFridge™

Commercially approved by  
- The pharmacy  
Guild of Australia  
QCPP



Quality Care Pharmacy  
program Compliance



This medical grade undercounter refrigerator optimised **safe** storage thanks to its double glazed glass panel that provides users full interior visibility.

This **Pharmacy Guild** approved Medifridge, allows for safe Temperature Control on all shelves for storage of vaccines, vitamins, and other sensitive products.



The Pharmacy  
Guild of Australia



# Product Features

- ◆ **Self-closing door**  
 To ensure constant temperature retention
- ◆ **Min/Max temperature recording**
- ◆ **Alarm (Audible & visual)**  
 Ensures items are not accidentally overexposed to warm temperatures
- ◆ **Factory installed lock**  
 Ensures additional security
- ◆ **LED lighting**  
 To optimise visibility for stored content and energy efficiency
- ◆ **Adjustable PVC coated shelves**  
 For easy positioning and cleaning
- ◆ **Airflow Shelving**  
 To ensure cool air is evenly distributed throughout the cabinet (improved airflow)
- ◆ **Fan-forced cooling system**  
 Ensures the temperature remains consistent throughout unit
- ◆ **Digital Thermostat**  
 For temperature accuracy and consistency

Model	MED0140GD	MED0220GD	MED0374GD
Part Number	3736213	3736217	3736218
Ext. Height (mm)*	820	1310	1840
Ext. Width (mm)*	595	595	595
Ext. Depth (mm)*	595	598	598
Capacity	145L	215L	372L
Temp. Range	+2°C - 8 °C	+2°C - 8 °C	+2°C - 8 °C
Plug Supplied	✓	✓	✓
Power Supply	10A	10A	10A
<b>Features</b>			
Internal Light	✓	✓	✓
Door Shape	Flat with Straight Corners	Flat with Straight Corners	Flat with Straight Corners
Feet Included	30mm Feet at Front. Rollers at back	30mm Feet at Front. Rollers at back	30mm Feet at Front. Rollers at back
No. of Shelves Incl. Base	4	4	4
Default Door Hinge	Right	Right	Right
<b>Warranty</b>			
Warranty	5	5	5



# Multi-Use USB Temperature Recorder

A cost effective and reliable solution which records data without special hardware or software


Track temperature variations for real-time information about your products

Connect the LogTag® to your device with its integrated, long-life USB connector

Analyse all recorded data in an automatically generated PDF or Excel report.

## Product Highlights

- Automatically generates a report  
 View data in a PDF report, excel file or an encrypted LogTag data file
- Fully user configurable  
 Individual alarm settings, start options, trip length and log interval
- Simply connects to your computer via USB
- Records up to 16,129 readings  
 Provides over 3 months logging at 10 minute sample intervals



# Specifications: LogTag® Data Logger

PART NUMBER	350700050
Measurement Range	-22° C - +70° C
Capacity	16,129 Real time temperature recording, non-volatile memory
Sampling Interval	2° C - 8 °C
Start Options	Push button start or specific date/time
Start up delay	Configurable from 1 minute to 72 hours
Environmental	IEC 60529: IP64 with USB cap fitted
Power Source	3V Lithium battery - non replaceable
Battery Life	2-3 years of normal use, based on 15 minute logging and monthly data download
Size	93mm(H) x 54.5mm (w) x 8.6mm (T) including USB cap
Weight	35g
Case Material	Polycarbonate
Alarm Functions	High/low, single, consecutive and cumulative alarm events, 'OK'/'ALERT' indicators
Connection Interface	USB 2.0, High durability, metal A-type plug
Software	Adobe Reader, LogTag Analyzer® 2.6 or higher

## Accuracy/Resolution Charts

